



6SS7

6SS7

**TRIPLE-GRID SUPER-CONTROL AMPLIFIER**

SINGLE-ENDED METAL TYPE

Heater	Coated Unipotential Cathode	
Voltage	6.3	a-c or d-c volts
Current	0.15	amp.
Direct Interelectrode Capacitances: ^o		
Grid to Plate	0.004 max.	μuf
Input	5.5	μuf
Output	7.0	μuf
Maximum Overall Length	2-5/8"	
Maximum Seated Height	2-1/16"	
Maximum Diameter	1-5/16"	
Bulb	Metal Shell, MT-8	
Base	Small Wafer Octal, 8-Pin	
Pin 1 - Shell		Pin 5 - Cathode
Pin 2 - Heater		Pin 6 - Screen
Pin 3 - Suppressor		Pin 7 - Heater
Pin 4 - Grid		Pin 8 - Plate
Mounting Position		Any



BOTTOM VIEW (8N)

AMPLIFIER

Plate Voltage	300 max.	volts
Screen Voltage	100 max.	volts
Screen Supply Voltage	300 max.	volts
Grid Voltage	0 min.	volts
Plate Dissipation	2.25 max.	watts
Screen Dissipation	0.35 max.	watt
<i>Typical Operation and Characteristics - Class A₁ Amplifier:</i>		
Plate Voltage	100	250 volts
Screen Voltage	100	100 volts
Grid Voltage	-1	-3 volts
Suppressor	Connected to cathode at socket	
Plate Res.	0.12	1.0 approx. megohm
Transcond.	1930	1850 μmhos
Grid Bias for Transcond.		
of 10 μmhos (approx.)	-35	-35 volts
Plate Cur.	12.2	9 ma.
Screen Cur.	3.1	2 ma.

- In circuits where the cathode is not directly connected to the heater, the potential difference between heater and cathode should be kept as low as possible.
- ° With shell connected to cathode.

May 1, 1941

RCA RADOTRON DIVISION
RCA MANUFACTURING COMPANY, INC.


TENTATIVE DATA

6SS7



6SS7

AVERAGE PLATE CHARACTERISTICS



APR. 3, 1941

RCA RADIOTRON DIVISION
RCA MANUFACTURING COMPANY, INC.

92C-6270